



LIFTING CAPACITY 3,500 to 4,500 lbs. • Installs without cutting up to 10"

S Hide-A-Way® Trailer Side Gate

> TRUE LEVEL RIDE



| TLS STANDARD FEATURES | BENEFITS |
|-------------------------------------------------------------|-------------------------------------------------------------|
| True Level Ride Lift Gate | Provides a Safer Working Environment for Driver and Freight |
| Power In and Out with Stainless Steel Chain | Designed to Reduce Road Calls |
| Automatic Over-the-Road Lock | Safely Secures Lift Gate in Over-the-Road Position |
| Adjustable to Trailer Dimensions | Ensures Custom Fit for Side Lift Gate |
| Accommodates Curb or Street Side of Trailer Installation | Flexibility to Meet Your Specific Delivery Requirements |
| Power Pack Enclosure | House Pump, Motor, and Room for Up to Four (4) Batteries* |
| Pressure Compensated Flow Control | Steady Hydraulic Pressure for Smooth Operation |
| Gravity Down | Reduces Power Usage and Motor Wear |
| Marine Potted Switches | Watertight Switches – Reduces Electrical Failure |
| Maintenance Minder2 | Measures and Records Lift Gate Operating Data |


* Based on Gate Width

Т

TRAILER SIDE LIFT



TLS Hide-A-Way® Trailer Side Gate



| PLATFORM WIDTH | DIMENSION "X" |
|----------------|---------------|
| 42" * | 60" |
| 48" | 66" |
| 60" | 78" |
| 72" | 90" |
| 80" | 98" |

TLS Technical Specs

| Model Number | Lifting Capacity | Platform Size | Main Platform | Secondary Platform | Rigid Ramp | Approx. Weight |
|---------------------|------------------|---------------|---------------|--------------------|------------|---------------------|
| TLS 3500 3,500 lbs. | 2 500 lbc | 42" W x 55" D | - - 51" D | 4" D | 10" Taper | TLS 3500 1,200 lbs. |
| | | 48" W x 55" D | | | | TLS 3500 1,300 lbs. |
| | 3,500 IDS. | 60" W x 55" D | | | | TLS 3500 1,450 lbs. |
| | - | 72" W x 55" D | | | | TLS 3500 1,600 lbs. |
| TLS 3510 | 3,500 lbs. | 80" W x 48" D | 48" Flat | No Secondary | 5" Taper | TLS 3500 1,800 lbs. |
| TLS 4500 | 4,500 lbs. | 42" W x 55" D | - 51" D | 4" D | 10" Taper | TLS 4500 1,250 lbs. |
| | | 48" W x 55" D | | | | TLS 4500 1,350 lbs. |
| | | 60" W x 55" D | | | | TLS 4500 1,500 lbs. |
| | | 72" W x 55" D | | | | TLS 4500 1,660 lbs. |

| AVAILABLE OPTIONS | | |
|-------------------|-----------------------------------------------------------------------------------|--|
| OPTION # | DESCRIPTION | |
| 111 | Additional Circuit Breaker for Supply Line | |
| 133 | Conversion Kit For Mounting to Aluminum Cross Members | |
| 134 | Mud Flap | |
| 142 | Dual Power Unit | |
| 154 | Reflecting Tape | |
| 155 | High Visibility Flashing Safety Lights along Lift Gate Arm, Nose Warning Light | |
| 261 | Emergency Hand Pump | |
| 265 | Power Unit Box Work Light | |
| 268 | Collapsible Safety Hand Rails (60" Minimum Width) | |
| 271 | Plug-In, Hand-Held Remote with Storage Box in Place of Upper Switch | |
| GV | Galvanized (Full Gate) | |
| GVP | Galvanized (Platform Only) | |
| P46622 | AGM Battery | |

| POWER KITS | | | |
|-----------------|------------------------------------------------------------------------------------------------|--|--|
| OPTION # | OPTION DESCRIPTION | | |
| 257-NG-30 | Power Kit: 30' "2" Gauge Cable – Dual Pole with Combo Box (Dual/Single Pole Receptacles) | | |
| 257-NG-45 | Power Kit: 45' "2" Gauge Cable – Dual Pole with Combo Box (Dual/Single Pole Receptacles) | | |
| 257-NG-60 | Power Kit: 60' "2" Gauge Cable – Dual Pole with Combo Box (Dual/Single Pole Receptacles) | | |
| 269-2B | Battery Hold-Down Kit - 2 Batteries for 42, 48, 60, 72, 80 Gate Width | | |
| 269-3B | Battery Hold-Down Kit - 3 Batteries for 60, 72, 80 Gate Width | | |
| 269-4B | Battery Hold-Down Kit - 4 Batteries for 72, 80 Gate Width | | |

* Only Gate Available for Pup Trailer