



TSG Technical Specs

LIFTING CAPACITY 3000 lbs.

• Floor Heights: 44" Laden to 56" Unladen

Model Number	Lifting Capacity	Platform Size	Main Platform	Secondary Platform	Ramp	Approx. Weight
TSG 3000	3,000 lbs.	54" W x 34" D	23" D	11" D	8" Taper	TSG 3000 800 lbs.
					Butt-End	
		72" W x 34" D	8" Taper		TSG 3000 830 lbs.	
			Butt-End			

TSG STANDARD FEATURES	BENEFITS
True Level Ride Lift Gate	Provides a Safer Working Environment for Driver and Freight
Manual Transit Lock	Safely Secures Lift Gate in Over-the-Road Position
Power Pack Enclosure	Houses Pump, Motor
Marine Potted Switches	Watertight Switches – Reduces Electrical Failure
Spring Assisted Opening and Closing	Ease of Use and Reduces Physical Effort to Operate
Greaseless Bushings	Reduces Maintenance Costs

AVAILABLE OPTIONS	
OPTION #	DESCRIPTION
111	Additional Circuit Breaker for Supply Line
143	Safety Cut Off Switch (In Cab)
201	Handheld Remote, Plugs into Receptacle
212	Drivers Step
213	12" Retention Ramp (Steel)
214	Maintenance Minder2
GV	Galvanized (Full Gate)
P46622	AGM Battery

POWER KITS	
OPTION #	POWER OPTION DESCRIPTION
125-NG	Power Kit: 27" "2" Gauge Cable – NO Trailer Plug