

## **LIFTING CAPACITY 4,500** – Designed to Reduce Road Calls

Floor Heights: 48" Laden/56" Unladen

PREMIER LPS Standard Features	Benefits
True Level Ride Lift Gate	Provides a Safer Working Environment for Driver and Freight
Galvanized Primary Platform, Aluminum secondary Platform & Retention Ramp	Prevents Rust
Power In and Out with Stainless Steel Chain	Designed to Reduce Road Calls
Flashing Safety Light on End of Platform	Safety Feature Provides Greater Visibility of Gate
Automatic Over-the-Road Lock	Safely Secures Lift Gate in Over-the-Road Position
Adjustable to Trailer Dimensions	Ensures Custom Fit for Side Lift Gate
Accommodates Curb or Street Side of Trailer Installation	Flexibility to Meet Your Specific Delivery Requirements
Power Pack Enclosure	Houses Pump, Motor, and Room for up to Four (4) Batteries*
Pressure Compensated Flow Control	Steady Hydraulic Pressure for Smooth Operation
Gravity Down	Reduces Power Usage and Motor Wear
Marine Potted Switches	Watertight Switches – Reduces Electrical Failure
Spring Assisted Opening and Closing	Ease of Use and Reduces Physical Effort to Operate





Hide-A-Way® Trailer Side Gate


## **PREMIER LPS** Technical Specs

Model Number	Lifting Platform Size		Primary Platform		Secondary Platform		Approx. Weight	Ramp	Vehicle Width	
Trainboi Capacity	W"	D"	W"	D"	W"	D"				
		72"	68"	72"	51.5"	72"	17"	1,650 lbs	15" Deep	96"
LPS 4500	4,500 lbs.	80"	76"	80"	51.5"	80"	25"	2,200 lbs	Retention	and
		86"	84"	86"	51.5"	86"	32"	2,500 lbs	Single/Dual	102"

PREMIER LPS Available Options			
OPTION #	DESCRIPTION		
111	Additional Circuit Breaker for Supply Line		
133	Conversion Kit For Mounting to Aluminum Cross Members		
134	Mud Flap		
142	Dual Power Unit		
154	Reflecting Tape		
155	High Visibility Flashing Safety Lights along		
214	Maintenance Minder2		
261	Emergency Hand Pump		
265	Power Unit Box Work Light		
268	Collapsible Safety Hand Rails		
270LPS-R1	1 Piece Retention Ramp Option for LPS		
270LPS-R2	2 Piece Retention Ramp Option for LPS		
271	Plug-In, Hand-Held Remote with Storage Box in Place of Upper Switch		
GV	Galvanized (Full Gate)		
P46622	AGM Battery		

PREMIER LPS Power Kits			
OPTION#	OPTION DESCRIPTION		
257NG-30	Power Kit: 30' "2" Gauge Cable – Dual Pole with Combo Box (Dual/Single Pole Receptacles)		
257NG-45	Power Kit: 451 "2" Gauge Cable – Dual Pole with Combo Box (Dual/Single Pole Receptacles)		
257NG-60	Power Kit: 60' "2" Gauge Cable – Dual Pole with Combo Box (Dual/Single Pole Receptacles)		
269-2B	Battery Hold-Down Kit - 2 Batteries for 42, 48, 60, 72, 80 Gate Width		
269-3B	Battery Hold-Down Kit - 3 Batteries for 60, 72, 80 Gate Width		
269-4B	Battery Hold-Down Kit - 4 Batteries for 72, 80 Gate Width		

## PREMIER LPS Minimum Mounting Space Requirements



PLATFORM WIDTH	DIMENSION "X"
72"	90"
80"	98"

